



MATERIAL SAFETY DATA SHEET

HELIUM

DATE: Dec 2018

1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Product Name	Helium
Chemical Formula	He
Trade Names	Helium, Technical (N2.7) Helium, High Purity (N4.5) Helium, Instrument, Grade (N4.5) Helium, UHP (5.0) Helium, Research (N6.0)
Colour Coding	Mid Brown (B.07) body with the appropriate grade decal affixed centrally to the body of the cylinder (N.B. Research grade Helium does not have a decal on the cylinder)
Valves	All grades have the Neriki – Brass 5/8 inch BSP right hand, positive pressure valves fitted.
Company Identification	Les Gaz Industriels Ltd Pailles Road G.R.N.W. – Republic of Mauritius Tel. No: (+230) 212 8306 Fax No: (+230) 212 0235

2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Helium
Chemical Family	Inert Rare Gas
CAS No.	7440-59-7
UN No.	1046
ERG No.	121
Hazchem Warning	2 C Non flammable gas

3 HAZARDS IDENTIFICATION

Main Hazards. All cylinders are portable gas containers, and must be regarded as pressure vessels at all times. Helium does not support life. It can act as a simple asphyxiant by diluting the concentration of oxygen in air below the levels necessary to support life.

Adverse Health Effects. Helium is non-toxic and inert. Inhalation in excessive concentrations can result in dizziness, nausea, vomiting, loss of consciousness, and death. Death may result from errors in judgement, confusion or loss of consciousness which prevents self-rescue. At low oxygen concentrations, unconsciousness and death may occur in seconds without warning.

Chemical Hazards. Helium is extremely inert and forms no known chemical compounds.

Biological Hazards. Helium is extremely light and disperses very rapidly into the atmosphere. No known hazard.

Vapour Inhalation. As Helium acts as a simple asphyxiant death may result from errors in judgement, confusion, or loss of consciousness which prevents self-rescue. At low oxygen concentrations, unconsciousness and death may occur in seconds without warning.

Eye Contact No known effects.

Skin Contact No known effects.

Ingestion (See "Vapour Inhalation" above).

4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to Helium. Rescue personnel should be equipped with self-contained breathing apparatus. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area, and given mouth-to-mouth resuscitation and supplemental oxygen.

Eye Contact No known effect.

Skin Contact No known effect.

Ingestion (See section above).

5 FIRE FIGHTING MEASURES

Extinguishing media As Helium disperses rapidly into the atmosphere, it would have little effect on the fire. The appropriate extinguishant should be used for the type of combustible material involved.

Specific Hazards Helium does not support life. It can act as a simple asphyxiant by diluting the concentration of oxygen in the air below the levels to support life.

Emergency Actions If possible, shut off the source of excess helium. Evacuate area. All cylinders should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. CONTACT THE NEAREST AFROX BRANCH.

Protective Clothing Self contained breathing apparatus. Safety gloves and shoes, or boots, should be worn when handling cylinders.

Environmental precautions. As the gas is lighter than air, ensure that it is not trapped in confined spaces, otherwise this could lead to the formation of an oxygen-deficient atmosphere. Ventilate all confined spaces using forced draught if necessary.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions Do not enter any area where Helium has been spilled unless tests have shown that it is safe to do so.

Environmental precautions Helium does not pose a hazard to the environment.

Small spills Shut off the source of escaping Helium. Ventilate the area.

Large spills Shut off the source of the spill if this can be done without risk. Restrict access to the area until completion of the clean-up procedure.

7 HANDLING AND STORAGE

Do not allow cylinders to slide or come into contact with sharp edges. Helium cylinders may be stacked horizontally provided that they are firmly secured at each end to prevent rolling. Use a "first in - first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Hazards. As Helium is a simple asphyxiant avoid any areas where spillage has taken place. Only enter once testing has proved the atmosphere to be safe.

Engineering Control measures. Engineering control measures are preferred to reduce the leakage of Helium into the atmosphere.

Personal protection Self-contained breathing apparatus should always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders.

Skin No known effect.

9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DATA

Chemical Symbol	He
Molecular Weight	4,0026
Specific Volume @ 20°C & 101,325 kPa	6030,4 ml/g
Relative density (Air = 1) @ 101,325 kPa	0,137
Colour	None
Taste	None
Odour	None

10 STABILITY AND REACTIVITY

Conditions to avoid Never use cylinders as rollers or supports, or for any other purpose than the storage of Helium. Never expose the cylinder to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.

Incompatible Materials. As Helium is inert it may be contained in systems constructed of any of the common metals which have been designed to safely withstand the pressures involved.

Hazardous Decomposition Products. None¹¹

TOXICOLOGICAL INFORMATION

Acute Toxicity	No known effect.
Skin & eye contact	No known effect.
Chronic Toxicity	No known effect.
Carcinogenicity	No known effect.
Mutagenicity	No known effect.
Reproductive Hazards	No known effect

(For further information see Section 3. Adverse Health Effects).

12 ECOLOGICAL INFORMATION

Helium does not pose a hazard to the ecology.

13 DISPOSAL CONSIDERATIONS

Disposal Methods Small amounts may be blown to the atmosphere under controlled conditions. Large amounts should only be handled by the gas supplier.

Disposal of packaging The disposal of cylinders must only be handled by the gas supplier.

14 TRANSPORT INFORMATION

ROAD TRANSPORTATION

UN No.	1046
ERG No.	121
Hazchem warning	2C Non-flammable gas

SEA TRANSPORTATION

IMDG	1046
------	------

Class	
Packaging group	
Label	Non-flammable gas

AIR TRANSPORTATION

ICAO/IATA Code	1046
Class	2.2
Packaging group	
Packaging instructions	
- Cargo	200
- Passenger	200
Maximum quantity allowed	
- Cargo	150kg
- Passenger	75kg

15 REGULATORY INFORMATION

EEC Hazard class	Non-flammable
Risk phrases	R20 Harmful by inhalation R44 Risk of explosion if heated under confinement
Safety phrases	S2 Keep out of reach of children S15 Keep away from heat S37 Wear suitable gloves S39 Wear eye/face protection S51 Use only in well ventilated areas

Refer to SABS 0265 for explanation of the above.

16 OTHER INFORMATION

Bibliography
Compressed Gas Association, Arlington, Virginia
Handbook of Compressed Gases - 3rd Edition
Matheson. Matheson Gas Data Book - 6th Edition
SABS 0265 - Labelling of Dangerous Substances

17 EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.

A member of The AFROX Group
For product and safety enquiries please phone
EMERGENCY N°:
+230 800 1133 (business hours)